

STABILITY CHAMBER(GMP)

- ◆ The latest airway system design achieves uniform of temperature and humidity form different parts inside the chamber.parts inside the chamber.
- ◆ Industrial compressor is European original imported completely sealed for high efficiency,low noise,assure machine of long time continuous running(SECOP).
- ◆ Temperature and humidity integrated sensor is European original imported for high precise, low floating annually.It can test humidity directly,no need of maintenance(VAISALA).
- ◆ Original imported controller,with accurate calibration function(ST590).
- ◆ Interior material is mirror stainless steel 304,no pollution source,easy for clean.
- ◆ Alarm system complies with GMP, High&low boundary deviation alarm for temperature&humidity.
- ◆ Date recording system complies with GMP,The standard needle type printer and USB flash memory.
- ◆ Interior material: Mirror surface Stainless steel 304; External material: Steel powder coated.
- ◆ Safety device: Compressor and blower overheat protection system, Over temperature protection, over pressure & overload protection for compressor, Water scarcity protection.
- ◆ Power source: AC 220V±10% 50Hz or 60HZ.
- ◆ Standard meets:ICH-2003 Q1(A)and CP2015.
- ◆ Temperature Accuracy: ±0.5 ; Temperature Deviation: ±1.0 ; Humidity Deviation: ±3%RH.



◆ 250SD



◆ 500SD

Model	Temperature Range()	Humidity Range(RH)	Capacity (L)	Interior dimensions W×D×H (mm)	External dimensions W×D×H(mm)	Power (kW)	Trays	Remarks
Labonce-150SD	0 ~ 65	40 ~ 95%	150	600×405×630	760×830×1500	1.2	3	
Labonce-250SD	0 ~ 65	40 ~ 95%	250	600×500×830	760×870×1650	1.5	3	
Labonce-400SD	10 ~ 65	40 ~ 95%	400	680×630×930	840×970×1750	2.0	3	
Labonce-500SD	10 ~ 65	40 ~ 95%	500	680×680×1080	840×1050×1850	2.2	4	
Labonce-150SD-II	10 ~ 65	40 ~ 95%	150	600×405×630	760×830×1500	1.2	3	Two compressor
Labonce-250SD-II	10 ~ 65	40 ~ 95%	250	600×500×830	760×870×1650	1.5	3	
Labonce-400SD-II	10 ~ 65	40 ~ 95%	400	680×630×930	840×970×1750	2.0	3	
Labonce-500SD-II	10 ~ 65	40 ~ 95%	500	680×680×1080	840×1050×1850	2.2	4	
Labonce-150LSD	10 ~ 65	20 ~ 95%	150	600×405×630	760×830×1500	1.2	3	
Labonce-250LSD	10 ~ 65	20 ~ 95%	250	600×500×830	760×870×1650	1.5	3	
Labonce-400LSD	10 ~ 65	20 ~ 95%	400	680×630×930	840×970×1750	2.0	3	
Labonce-500LSD	10 ~ 65	20 ~ 95%	500	680×680×1080	840×1050×1850	2.2	3	
Labonce-150LSD-II	10 ~ 65	20 ~ 95%	150	600×405×630	760×830×1500	1.2	3	Two compressor
Labonce-250LSD-II	10 ~ 65	20 ~ 95%	250	600×500×830	760×870×1650	1.5	3	
Labonce-400LSD-II	10 ~ 65	20 ~ 95%	400	680×630×930	840×970×1750	2.0	3	
Labonce-500LSD-II	10 ~ 65	20 ~ 95%	500	680×680×1080	840×1050×1850	2.2	4	