

## STABILITY CHAMBER(GMP)

- ◆ The latest airway system design achieves uniform of temperature and humidity form different parts inside the chamber.parts inside the chamber.
- ◆ Industrial compressor is European original imported completely sealed for high efficiency,low noise,assure machine of long time continuous running(SECOP).
- ◆ Temperature and humidity integrated sensor is European original imported for high precise, low floating annually.It can test humidity directly,no need of maintenance(VAISALA).
- ◆ Original imported controller,with accurate calibration function(ST590).
- ◆ Interior material is mirror stainless steel 304,no pollution source,easy for clean.
- ◆ Alarm system complies with GMP, High&low boundary deviation alarm for temperature&humidity.
- ◆ Date recording system complies with GMP,The standard needle type printer and USB flash memory.
- ◆ Interior material: Mirror surface Stainless steel 304; External material: Steel powder coated.
- ◆ Safety device: Compressor and blower overheat protection system, Over temperature protection, over pressure & overload protection for compressor, Water scarcity protection.
- ◆ Power source: AC 220V±10% 50Hz or 60HZ.
- ◆ Standard meets:ICH-2003 Q1(A)and CP2015.
- ◆ Temperature Accuracy: ±0.5 ; Temperature Deviation: ±1.0 ; Humidity Deviation: ±3%RH.



◆ 800SD-2000SD

Model	Temperature Range( )	Humidity Range(RH)	Capacity (L)	Interior dimensions W×D×H (mm)	External dimensions W×D×H(mm)	Power (kW)	Trays	Remarks
Labonce-800SD	10 ~ 65	40 ~ 95%	800	1200×510×1300	1350×870×1880	2.5	4	DIGITAL DISPLAY METER
Labonce-1000SD	10 ~ 65	40 ~ 95%	1000	1400×510×1400	1560×870×1980	3.0	4	
Labonce-1500SD	10 ~ 65	40 ~ 95%	1500	1500×710×1400	1650×1070×1980	3.5	4	
Labonce-2000SD	10 ~ 65	40 ~ 95%	2000	1500×970×1380	1650×1330×1980	3.8	4	
Labonce-800SD-II	10 ~ 65	40 ~ 95%	800	1200×510×1300	1350×870×1880	2.5	4	
Labonce-1000SD-II	10 ~ 65	40 ~ 95%	1000	1400×510×1400	1560×870×1980	3.0	4	
Labonce-1500SD-II	10 ~ 65	40 ~ 95%	1500	1500×710×1400	1650×1070×1980	3.5	4	
Labonce-2000SD-II	10 ~ 65	40 ~ 95%	2000	1500×970×1380	1650×1330×1980	3.8	4	
Labonce-800LSD	10 ~ 65	20 ~ 95%	800	1200×510×1300	1350×870×1880	2.5	4	LOW HUMIDITY
Labonce-1000LSD	10 ~ 65	20 ~ 95%	1000	1400×510×1400	1560×870×1980	3.0	4	
Labonce-1500LSD	10 ~ 65	20 ~ 95%	1500	1500×710×1400	1650×1070×1980	3.5	4	
Labonce-2000LSD	10 ~ 65	20 ~ 95%	2000	1500×970×1380	1650×1330×1980	3.8	4	
Labonce-800LSD-II	10 ~ 65	20 ~ 95%	800	1200×510×1300	1350×870×1880	2.5	4	
Labonce-1000LSD-II	10 ~ 65	20 ~ 95%	1000	1400×510×1400	1560×870×1980	3.0	4	
Labonce-1500LSD-II	10 ~ 65	20 ~ 95%	1500	1500×710×1400	1650×1070×1980	3.5	4	
Labonce-2000LSD-II	10 ~ 65	20 ~ 95%	2000	1500×970×1380	1650×1330×1980	3.8	4	