

## Electric Heating Thermostatic Incubator (DHP Series)

Labonce-DHP electric thermostat incubator is used in medical and health care, pharmaceutical industry, biochemistry and agricultural science and other scientific research and industrial production departments to do bacteria culture, fermentation and constant temperature test.

- ◆ Reference standard: YY 0027-1990 electrothermal incubator;
- ◆ Heating method: Air jacket electric heating, fast heating speed;
- ◆ Chamber Materials: The exterior is coated with high quality steel plate, The liner is made of mirror stainless steel, four corners half circle arc over plating, shelf can be free loading and unloading;
- ◆ Control System: High precision microcomputer digital display controller with timing function;
- ◆ External door design: double doors with built-in glass doors for easy observation of culture changes;
- ◆ Controlling Temperature Precision: Temperature resolution: 0.1 °C ; Temperature uniformity  $\pm 1.5$  °C (@ 37 °C);
- ◆ Environment Temperature: +5 ~ 35°C ;
- ◆ Power: AC220V $\pm$ 10% 50HZ;
- ◆ **Optional:** Touch screen controller with three-level permissions and audit tracking.



Name	Model	Temperature Range (°C)	Capacity (L)	Interior Dimensions(mm) W×D×H	External Dimensions(mm) W×D×H	Power (kW)	Shelf (Standard)	Remarks
Electrothermal Incubator	Labonce-9052DHP	RT+5 ~ 65	50	415×360×355	690×500×500	0.3	2	
	Labonce-9082DHP	RT+5 ~ 65	80	500×400×400	780×530×560	0.4	2	
	Labonce-9162DHP	RT+5 ~ 65	160	500×500×650	790×630×810	0.6	2	
	Labonce-9272DHP	RT+5 ~ 65	270	600×600×750	890×740×910	0.8	2	
	Labonce-9402DHP	RT+5 ~ 65	400	640×585×1355	780×750×1880	1.1	3	
	Labonce-9602DHP	RT+5 ~ 65	600	840×600×1355	980×800×1880	2.2	4	